



# Galaxy J3 prime LCD Screen Replacement

How to take apart galaxy J3 Prime

Written By: Brian Brown

## INTRODUCTION

in this guide, you will learn how to completely take apart a galaxy J3 prime and put it back together

there is a video above to help you if you have any problems

---

### TOOLS:

- [Spudger](#) (1)
- [Heat Gun](#) (1)
- [Small phillips head screw driver](#) (1)
- [Tweezers](#) (1)

## Step 1 — remove the back cover and the battery



- Insert wisdom here.

## Step 2 — heat up screen with hair dryer for about 3 minutes



- Insert wisdom here.

### Step 3 — put on gloves so u don't burn your hands



- Insert wisdom here.

### Step 4 — get a spudger and use it to put in between phone frame and front display



- Insert wisdom here.

**Step 5 — u will notice plastic bracket, remove that when prying up screen**



- Insert wisdom here.

**Step 6 — gently pull up on lcd screen adhesive to remove screen**



- Insert wisdom here.

**Step 7 — remove screws on back of phone frame that is holding housing of phone together**



- Insert wisdom here.

**Step 8 — now that all of the screws are removed, pull up on frame with screwdriver and or spudger**



- do it gently so you dont break anything

## Step 9 — remove motherboard from metal housing



- disconnect metal flexcable from charging port

## Step 10 — remove motherboard with spudger



- Insert wisdom here.

---

To reassemble your device, follow these instructions in reverse order.

This document was last generated on 2018-06-23 03:40:26 AM.