



# Motorola Adventure V750 Front Glass Replacement

A step by step guide in replacing the front glass on a Motorola Adventure V750 cellular phone.

Written By: Kyle



## INTRODUCTION

The glass covering on mobile devices can be prone to damage and constant wear and tear. The Motorola Adventure V750 has a very moderate process in replacing the front protection screen.

---

### TOOLS:

- [64 Bit Driver Kit](#) (1)
-

## Step 1 — Front Glass



- ① Remove the back cover and battery of the Motorola Adventure V750.

## Step 2



- Remove four screws that are visible using a screwdriver.

### Step 3



- After removing the battery chamber, you can unclip one of the ribbons that connect the screen to the main body of the phone. This divides the phone into two halves.

### Step 4



- Remove two screws located at the bottom of the main display.

## Step 5



- Now the display(screen) can be removed by sliding a sharp object or fingernail along the edge of the housing. This releases the clip attached to the screen.

## Step 6



- Release the display up to the point where you see two metal parts (left and right of the Motorola text). The top part of the display is held on with double sided tape.

## Step 7



- Gently unstick the tape and remove the display. Be careful not to bend this part.

## Step 8



- Carefully install the new glass.

---

To reassemble your device, follow these instructions in reverse order.

This document was last generated on 2018-04-01 01:08:52 PM.