



iPhone 4 Verizon Rear Panel Replacement

Replace a rear panel on your iPhone 4 Verizon.

Written By: Andrew Bookholt



INTRODUCTION

Remove the rear panel to access components inside your iPhone 4.

[video: http://www.youtube.com/watch?v=_z1AgyEaefQ]



TOOLS:

- P2 Pentalobe Screwdriver iPhone (1)



PARTS:

- iPhone 4 Revelation Kit (CDMA/Verizon) (1)

Step 1 — Rear Panel



- ⚠** Before you begin, discharge your iPhone battery below 25%. A charged lithium-ion battery can catch fire and/or explode if accidentally punctured.
- Power off your iPhone before beginning disassembly.
 - Your phone's rear cover may have two #000 Phillips screws **or** Apple's 5-Point "Pentalobe" screws. Check which screws you have, and ensure you also have the correct screwdriver in order to remove them.
 - Remove the two 3.6 mm Pentalobe or Phillips #000 screws next to the dock connector.

Step 2



- Push the rear panel toward the top edge of the iPhone.
- ⓘ The panel will move about 2 mm.

Step 3



- Pinch the rear panel with your fingers, and lift it away from the iPhone. Alternatively, use a Small Suction Cup .
- ⚠ Be careful not to damage the plastic clips attached to the rear panel.

To reassemble your device, follow these instructions in reverse order.