



LG VS810 Screen Replacement

Replace the screen for the LG VS810.

Written By: Galaipa



 **TOOLS:**

- [Heat Gun \(1\)](#)
- [Spudger \(1\)](#)
- [Phillips #00 Screwdriver \(1\)](#)

 **PARTS:**

- [LG L Fino F60 D390N Full Screen \(1\)](#)

Step 1 — Remove back cover



- Remove the back cover

Step 2



- Remove the battery , SIM card, and SD card

Step 3



- Unscrew the 8 screws using a Phillips (PH#00) screwdriver
- Using a plastic opening tool , once again pry up on the edges of the plastic back cover.
- ⓘ Working on a magnet board is recommended as the screws are small and can be easily misplaced

Step 4 — The motherboard




- Gently disconnect the screen cable using a spudger.
- Using the spudger, pry the motherboard away from the screen assembly.

Step 5 — Display Assembly



- Use a heat gun or hairdryer to heat up the edges. This will loosen the glue so the screen can be removed.
- Continue to heat and separate until the screen comes completely apart from the rest of the phone using plastic tools

 The phone will be extremely hot. Avoid direct contact with metal pieces.

To reassemble your device, follow these instructions in reverse order.

This document was last generated on 2018-04-19 03:06:40 AM.