



Saeco Royal Opening Procedure

Opening a Saeco Royal

Written By: VauWeh



INTRODUCTION

This section describes how to open the machine for further repairs.

TOOLS:

- [Phillips #2 Screwdriver](#) (1)
 - [T10 Torx Screwdriver](#) (1)
 - [T15 Torx Screwdriver](#) (1)
-



Step 1 — Preparing



 Unplug!

- Remove all attachments like water tank, brewing unit etc.

Step 2 — Top




- The coffeebean supply is fixed with two screws. Unscrew them and lift it off.
- The adjuster of the grinder has to be solved. Mark the position or just take a picture. This type is fixed with a screw, others are only stucked together.

Step 3 — Rear side





- There are two screws to be turned out.

Step 4 — Front



- The screws are situated on the underneath of the cover. This type is held by four screws.

Step 5 — Lift cover off



- Now the cover can be raised: first grip on left and right rear side and lift about 10 cm. Sometimes the cover jams a little bit.
- Solve the hoses which lead to the water tank. Sometimes you have to pull out some contacts, (e.g. the yellow-green protection lead), don't forget to put it on later.
- The cover can be drawn aslant towards the front, sliding it over the hot water pipe.
- Most repairs can be done with the cover being laid up partially, it must not be completely removed.

And now follow all steps in reverse order.